



## EVERPURE 2FC-P DRINKING WATER SYSTEM

COMMERCIAL GRADE WATER FILTRATION FOR HOME



The 2FC-P Cartridge is Tested and Certified by NSF International against NSF/ ANSI Standards 42 and 53 for the reduction of:

STANDARD NO 53-

HEALTH EFFECTS

Chemical Reduction Lead

Mechanical Filtration

Cyst

STANDARD NO. 42 — AESTHETIC EFFECTS Bacteriostatic Effects

Chemical Reduction Taste & Odor Chlorine

Mechanical Filtration

Nominal Particulate Class I

STANDARD NO. 401 — EMERGING COMPOUNDS / INCIDENTAL CONTAMINANTS Mechanical Filtration Microplastics



The model 2FC-P is certified by IAPMO R&T against NSF/ANSI 53 for the reduction of Perfluorooctanoic acid (PFOA) and Perfluorooctane sulfonate (PFOS).





The 2FC-P water filtration cartridge featuring exclusive FibredyneTM media is designed to reduce PFOA/PFOS, chlorine, taste & odor, lead, microplastics and particulates. These features can help ensure reliable, long-lasting equipment performance. The system using this cartridge can maintain a flow rate of 1.5 gpm for 1,000 gallons.

## FEATURES • BENEFITS

- Proprietary Fibredyne™ media reduces chlorine, taste & odor while providing particulate reduction down to 0.2 micron\*
- Certified to reduce up to 99.8% of PFOA/PFOS, commonly known as "forever chemicals"
- Reduces lead below the U.S. Federal Action Level of 15 ppb, and and the Health Canada level of 5 ppb
- NSF/ANSI Standard 42 certified for the reduction of Chlorine, Taste & Odor, and Particulate Class I
- NSF/ANSI Standard 53 certified to reduce cysts such as Cryptosporidium and Giardia by mechanical means
- NSF/ANSI Standard 401 certified for Microplastics Reduction
- Certified by IAPMO R&T against NSF/ANSI 53 for the reduction of Perfluorooctanoic acid (PFOA) and Perfluorooctane sulfonate (PFOS)

## MAINTENANCE REQUIREMENTS

 Replace cartridge when capacity is reached, or when flow becomes too slow. To ensure optimum water filtration, cartridges should be changed annually.

## WARRANTY

Everpure Pentair Components are warranted to be free of defects for a full twelve (12) months after purchase.

MODEL	PART NO	DESCRIPTION
2FC-P	EV2FCPS	Drinking Water System
2FC-P	EV959511	Replacement Cartridge

\*Validated by ISO 17025 accredited lab for 99.999% reduction of Brevundimonas diminuta following the ASTM F838 protocol for the validation of 0.2 µm sterilizing grade filters.

EPA Est. 002623-IL-002

Note: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.